



Car Vision® Camera CVC210AXL

Quality First For Performance That Lasts

Pick Up Element

1/3" CCD

Pixel Count

512 (H) x 492 (V)
(251,904 total pixels)

Lens

2.0mm f2.5 electronic iris

Minimum Illumination

0.3 lux (0.03 ft. candles)

Resolution

Horizontal: 380 lines
Vertical: 350 lines

Field of View

Horizontal: 115°
Vertical: 84°

Shock and Vibration

9.0G @ 0-2000 cpm

Operating Conditions

All weather operation

Weight

5 oz.

Dimensions

(with mounting bracket)
W x H x D
2.70" x 5.00" x 2.32"

(without mounting bracket)
W x H x D
1.98" x 1.98" x 2.32"

Color

Wimbledon White

Options

Chrome Housing
Heater

Warranty

Five years parts & labor
Extended warranty available
at time of purchase

Audio Equipped Extended Life Mobile Safety Camera

Intec's CVC210AXL camera provides a large field of view for the most demanding applications. The small size and variety of mounts make it a great camera for both rear and side vision and the multiple-sealed case and connector guarantee waterproof performance for 5 years.

Product Benefits

- **Watertight Military Spec Connector** ensures complete moisture protection.
- **Heavy Duty** cast aluminum alloy enclosure resists weather and impact.
- **Compact Size** for easy inconspicuous installation. Fits where other cameras won't.
- **One-Way Audio** allows the driver to hear activity around the vehicle.
- **Five Year Warranty** covers this heavy-duty extended life camera.

Instant Spec

The black and white camera shall be an Intec Model CVC210AXL. The camera shall incorporate a 1/3" high density CCD interline transfer pickup device with at least 251,904 [512 (H) x 492 (V)] pixels. The camera shall produce a horizontal resolution of at least 380 lines. The camera shall feature an Automatic Gain Control (AGC) circuit to provide clear images in low light conditions. The camera shall deliver a usable black and white picture at a scene illumination of 0.3 lux. The camera shall provide a horizontal field of view of at least 115° and a vertical field of view of at least 84°. The camera/cable connection shall be qualified to MIL-C26482, Series 1, the male pressurized receptacle shall be installed into the camera case, rendering a watertight connection/enclosure. The camera shall have a shock/vibration rating of at least 9.0G @ 0-2000 cpm and be able to transmit images to a monitor using a single cable. The camera shall carry at least a five year warranty.

The CVC210AXL Camera is compatible with all standard **INTEC** CVM Series Monitors (some may require adapter).



For service and literature:
www.intecvideo.com
West: 800-468-3254
East: 800-522-5989

Intec Video Systems, Inc.
23301 Vista Grande
Laguna Hills, CA 92653

CVC210AXL SPEC 02/08

Intec® and Car Vision® are registered trademarks of Intec Video Systems, Inc.

© 2008 Intec Video Systems, Inc.

Specifications Subject to Change
Without Prior Notice.