

CVH Series

Cables



Your Car Vision CVH Series Cables



are designed and constructed for reliable performance across a range of applications. The cables' outer jackets are Polyurethane and resistant to cuts, abrasions, solvents and oils. All connections are IP67, when mated, and offer protection against dust and water penetration when submerged up to 1 meter deep for a half hour.

Built-in lock/release mechanism securely locks mated connectors while allowing quick disconnection by simply pulling on the plug's release collar. Glass reinforced thermoplastic compounds and noncorrosive components are used in all assemblies.

Multiple polarizing keys protect the contacts from misalignment or attempted insertion of the wrong connector, while assuring correct mating between the corresponding connectors.

The CVH series of cables are available in a number of standard lengths and configurations allowing for easy installation in a variety of applications. In addition, custom lengths and configurations are available.

For additional information call
(west) 800.468.3254 or
(east) 800.522.5989

		
Model	CVH Cable	CVHMF - Extension Cable
Use With	H Series Controllers, Cameras, and Displays	
Maximum Length	280 Feet (85 Meter) Combined	
Connector	Hirose	
Cable Diameter	0.20" (5.08mm)	
Operating Temperature	-40° to +176° F (-40° to +80° C)	
Bend Radius	180° @ 1.60" (40.64mm)	
Shore Durometer	81A	
Wire Gauge	26 and 28 AWG	
Chemical Resistance	Excellent	
Abrasion Resistance	Excellent	
Warranty	Two Years	
Applications	Recreational / Commercial	
Standard Lengths and Part Numbers	3 Meter - CVH3MA 6 Meter - CVH6MA 11 Meter - CVH11MA	3 Meter - CVHMF3MA 8 Meter - CVHMF8MA 15 Meter - CVHMF15MA
Custom Lengths Available Upon Request.	16 Meter - CVH16MA 21 Meter - CVH21MA 30 Meter - CVH30MA	



Quality first for performance that lasts

www.intecvideo.com

Corporate: 23301 Vista Grande, Laguna Hills, CA 92653 | Eastern: 4256 State Route 51 North, Belle Vernon, PA 15012